



**AFINIA LABEL®**  
**MAKE YOUR OWN LABELS**

**CP950**  
ENVELOPE & PACKAGING PRINTER

# CP950 Envelope and Packaging Printer

## Print directly on packaging and thicker media

The CP950 Envelope and Packaging Printer is built with Memjet's Sirius print engine, featuring a stationary printhead for ultimate speed, quality, and reliability. The printhead can be raised or lowered, allowing for printing on a range of porous and inkjet-coated media substrates of varying thicknesses (up to 10 mm).

### Key Features

- ✓ Accepts media up to 10mm in thickness
- ✓ Industry-leading ink cost
- ✓ Fast print speeds up to 12 in/sec
- ✓ Adjustable printhead height

### Water-Resistant Inks

The CP950 Plus model has Watershield™ for increased moisture resistance.

This optional technology is perfect for prints that may be exposed to moisture, such as chilled or frozen foods, chemicals, or pharmaceutical products.



### Intuitive Touchscreen Control Panel

Large 7" digital display makes control and system status simple

### Thickness adjustment

Allows for materials from paper-thin to 10mm (3/8") thick

### Memjet-powered stationary printhead

Enables ultimate speed, quality, and reliability

### Range of output options

Output tray included, larger conveyor options available

### Easy access

For simplified maintenance and servicing



[afinialabel.com](http://afinialabel.com)

**US Office**  
sales@afinialabel.com  
+1 888.215.3966



**UK Office**  
sales@afinia.co.uk  
+44 (0) 845.250.7949



**AFINIA LABEL®**

# CP950 Specifications

## Printer:

<b>Print method:</b>	Memjet Waterfall Printhead Technology® 11 Integrated Circuit (IC) Chips – 70,400 nozzles
<b>Inks:</b>	Dye-based, 250mL CMYKK cartridges (1.25L total)
<b>Print resolution:</b>	1600x1600 dpi to 1600x800 dpi
<b>Print speed:</b>	6"–12" per second (152mm–305mm)
<b>Print area (max):</b>	8.77" x 45" (222.8mm x 1143mm)

## Media:

<b>Media types:</b>	Compatible with a range of inkjet-receptive paper, polyester, polypropylene, and vinyl materials
<b>Media width:</b>	3"–10.5" (76mm–266.7mm)
<b>Media length:</b>	4.2"–14.25" (107mm–362mm)
<b>Thickness:</b>	0.004"–0.4" (0.1mm–10mm)
<b>Feeder Capacity:</b>	Up to 500 single sheets or 750 #10 envelopes

## General:

<b>Interfaces:</b>	USB 2.0, Ethernet Port
<b>Ink Monitor:</b>	Viewable on 7" Touchscreen Display and CP950 Toolbox
<b>Operating System:</b>	Windows Printer Drivers for Windows; 8, 8.1, 10
<b>Diagnostics:</b>	Viewable on 7" Touchscreen Display and CP950 Toolbox
<b>Data Storage:</b>	Onboard Printer Storage for Job Library
<b>Firmware Update:</b>	Flash update through CP950 Toolbox
<b>Operating temperature:</b>	15°–35°C (59°–95°F) at RH 20–80%
<b>Storage temperature:</b>	–5°–50°C (23°–113°F) at RH up to 85%, non-condensing at 65°
<b>Duty Cycle</b>	350,000 letter-sized/A4 sheets per month
<b>Overall dimensions:</b>	21-1/8" W x 39" L x 20-1/4" H (53.6 cm x 99.1 cm x 51.4 cm)
<b>Weight:</b>	95 lbs. (43.9 kg)
<b>Electrical:</b>	100-240 VAC, 50/60 Hz
<b>Options:</b>	Conveyor/Stacker, Conveyor Drop Tray, Printer Drop Tray
<b>Warranty:</b>	One year



**In-House Label Solutions for Every Level of Production**

[afinialabel.com](http://afinialabel.com)

**US Office**  
sales@afinialabel.com  
+1 888.215.3966



**UK Office**  
sales@afinia.co.uk  
+44 (0) 845.250.7949

**AFINIA LABEL®**