

TROJAN<sup>™</sup>  
**T2-C**

- Intuitive High Volume Tabletop Press
- Print Labels Up To 8.8" Wide



## First Tabletop Press Designed with Full Capacity of a Larger Press

- Fast print speed up to 12 inches per second (60 ft per minute)
- Superior print resolution up to 1600 dpi
- Print width 2" to 8.8"
- First tabletop press to operate at the high-volume capacity and precision of a digital press

The T2-C is our first high capacity tabletop label press. Opening new doors in the industry, tabletop label printers cannot compare to the volume, quality and precision offered by the T2-C. Utilizing all the capabilities of the T2 Digital Press, the T2-C easily fits into any size print department, producing consistent, high-volumes at 24/7 production.

The new straight feed feature allows for precision printing even at higher volumes, removing wasted labels entirely. A plug and print solution, the T2-C is self-aligned with tension control, making set up hassle free. With the T2-C, you have the option to print pre-die cut blanks or print on continuous material, according to your production schedules. Ideal for brand owners, print shops and smaller label converters looking to add high resolution color inkjet labels to their portfolio.

# Trojan T2-C Specifications

## Operation:

<b>Ink Type:</b>	Dye ink, (4) individual CMYK tanks
<b>Print Resolution:</b>	1600 x 800 dpi or 1600 x 1600 dpi
<b>Print Speed:</b>	6 ips (150 mm/sec) or 12 ips (300 mm/sec)
<b>Print Area:</b>	Width: 8.8" (223 mm) Length: 0.6" (15 mm) – 60" (1525 mm) without stitching, unlimited length with stitching
<b>Media Sensors:</b>	Optical tracking edge sensor, adjustable position. Black mark sensor, gap sensor and continuous
<b>Connectivity:</b>	Ethernet 10/100/1000
<b>Software:</b>	TrojanControl Software Microsoft Windows® 10, 8, 7; Windows Server® 2012, 2008, 64/32-bit Drivers

## Environmental & Physical:

<b>Printer Operating:</b>	Operation: 59° F to 86° F (15° C to 30° C) at RH 22 to 80%(non-condensing) Storage: 41° F to 122° F (5° C to 50° C) at RH up to 85%, non-condensing at 149° F (65° C)
<b>Power Requirements:</b>	100-240V AC – 50/60 Hz (360W, 2.5A power supply)
<b>Aerosol extraction system:</b>	Yes, replaceable filters
<b>Dimensions (with with 250 ml internal ink cartridges, standard):</b>	23.8" L x 22.8" W x 23.4 H (606 mm x 580 mm x 595 mm)
<b>Dimensions (with 2 liter external ink tanks, option):</b>	23.8" L x 22.8" W x 31.3 H (606 mm x 580 mm x 795 mm)
<b>Touchscreen:</b>	7" touchscreen
<b>Weight:</b>	132.3 lbs. (60 kg) without ink and label roll
<b>Optional Accessories:</b>	RIP workflow/color management software Artwork designer software (Variable data)

## Supplies:

<b>Ink:</b>	CMYK tanks, 2 Liters each
<b>Maintenance Cartridge:</b>	Maintenance tray with replaceable modules (wiper roller/print head cap)
<b>Ink Type:</b>	High performance, water-based dye inks with extra wide color gamut that produce true-to-life color when combined with QuickLabel approved media

## Labels:

<b>Width:</b>	1.9" (50 mm) – 9.8" (250 mm)
<b>Length (Die-cut):</b>	0.6" (15 mm) – 60" (1525 mm)
<b>Thickness:</b>	4pt/mil to 12 pt/mil
<b>Roll Size:</b>	Max 12" (300 mm), 3" (76 mm) core
<b>Types:</b>	Paper, Inkjet coated gloss paper, PE, PET, PP

## Warranty:

Printer: 12 Month Manufacturer's Parts & Labor Warranty (excludes wear parts and supplies).



Powered by  memjet®

**QuickLabel | Toll-free: 877-757-7978 | Tel: +1 401-828-4000**  
**info@quicklabel.com | www.quicklabel.com**